



NOT HOTTM

COLD SILVER SOLDER

This is a method of attaching wires to a buried metal pipeline without using typical methods that generate heat on the pipeline during wire attachment.

There is a need to have an alternative to thermo-welding or brazing in specific instances when use of heat related wire attachment is unsafe or undesirable.

ADVANTAGES

- Low resistant electrical connection without welding or heat involved. Uses a magnet and conductive epoxy.
- Fits to any sized pipeline.
- Avoids potential damage if plastic pipe insertion is unknown.
- Can be used when pipe wall thickness is thin.
- No risk of ignition in high risk combustible environments.
- Keyhole compatible installation using the NotHot keyhole applicator tool
- Low profile connection on pipeline reduces risk of soil stress damage to the connection.
- Compatible with a variety of coating patch products.

FEATURES

This alternative method of pipeline wire attachment consists of a pre-manufactured metal saddle constructed with a factory attached silver soldered wire and embedded neodymium magnet. The metal saddle is then placed on the prepared pipeline with conductive epoxy to provide a “cold solder” to further enhance the connection. The strong magnet holds the saddle in place while the conductive epoxy cures. Both provide conductivity.



ARIZONA
7310 North 108th Avenue | Glendale, AZ. 85307
Phone: (623) 486-7800 | Fax: (623) 486-7827

CALIFORNIA
341 Stealth Court | Livermore, CA 94551
Phone: (925) 271-2008

9360 7th St. Suite B | Rancho Cucamonga, CA 91730
Phone: (623) 486-7800

www accurat corrosion.com

(Patent No. US011231303B2)